



FLIR IP67 Housing
for A40/A50/A70 thermal cameras

Key Features:

- Designed for FLIR A40/A50/A70 and/or FLIR A400/A500/A700 thermal automation cameras
- Camera accuracy remains within standard specifications with FLIR's proprietary radiometric formulas
- Aluminum (IP67) or stainless steel (IP69k) construction with germanium window
- IP69k enclosure: made of A316L electro-polished to Ra <0.8 μm; all seals are made of FDA certified material

Note: The germanium window blocks the visual camera except when using T912493

SPECIFICATIONS

Overview	T912302	T912301
Compatible cameras	FLIR A40/A50/A70	FLIR A40/A50/A70
Aperture IR	41.9 mm	43 mm
IR Window coating	Outside: DLC; Inside: AR	
IR Window material	Germanium	
Visual Window aperture	-	-
Visual Window coating	-	-
Cable gland	Stainless steel AISI 303 with TPE insert. Optional EHEDG certified cable gland in stainless steel, A316L, with food grade TPU insert and seal	Brass, nickel-plated with TPE-V inserts
Cable gland thread	M20	M25
Conformity	RoHS, REACH, EHEDG [†]	RoHS, REACH
Encapsulation	IP69K	IP67
Gaskets on housing	EPDM, hygienic, FDA certified	EPDM
Material	Stainless steel A316L	Aluminum, 6000-series
Surface treatment	Electro-polished, Ra <0.8 μm	Type II, natural anodized
Mounting	1x sides, 3x m6, cc 25 mm, depth 5 mm	4x sides, 4x m6, cc 25 mm, depth 5 mm
Size (L x D)	188.6 x 80.0 mm (7.43 x 3.15 in)	187.2 x 80.0 mm (7.37 x 3.15 in)
Weight	3.45 kg (7.61 lbs)	1.3 kg (2.87 lbs)

	T912493	T912366
Compatible cameras	FLIR A40/A50/A70	FLIR A400/A500/A700
Aperture IR	24.4 mm x 17.2 mm	39 mm
IR Window coating	Outside: DLC; Inside: AR	
IR Window material	Germanium	
Visual window aperture	9.4 mm x 7.2 mm	
Visual window coating	Inside AR Visual window material - Borosilicate Crown Glass	
Cable gland	Brass, nickel-plated with TPE-V inserts	
Cable gland thread	M25	
Conformity	RoHS, REACH	
Encapsulation	IP67	
Gaskets on housing	EPDM	
Material	Aluminum, 6000-series	
Surface treatment	Type II, natural anodized	
Mounting	4x sides, 4x m6, cc 25 mm, depth 5 mm	
Size (L x D)	187.2 x 80.0 mm (7.37 x 3.15 in)	220.3 x 111 mm (8.67 x 4.37 in)
Weight	1.3 kg (2.87 lbs)	2.1 kg (4.63 lbs)



FLIR IP67 Housing
for A40/A50/A70 thermal cameras



IP67/IP69K HOUSINGS

Protective Housings for FLIR Automation Cameras



Specifications subject to change. For the most up-to-date specifications, please visit flir.com.

For technical or sales support, please visit:
www.flir.com/about/general-inquiries

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 02/27/25
IP67-IP69k_Housings_Datasheet-LTR 25-0124-INS