



3 MEGA PIXEL CORNER CAMERA

Ariel™ 3MP Corner




The Ariel™ 3MP Corner Camera features a unique corner-shape form factor and extended field of view lens that provides ceiling-to-floor and wall-to-wall coverage. Due to its corner mounting, ligature-free housing and discrete infrared illumination, the Ariel 3 MP Corner camera is an ideal solution for any deployment that requires full coverage from a single camera — including correctional institutions, healthcare facilities, building lobbies and elevators.

www.flir.com/security



DURABLE HOUSING

A rugged, no-ligature housing resists tampering, yet its sleek design makes it suitable for both industrial and commercial locations.



EXTENDED FIELD OF VIEW

The camera's specialty lens provides ceiling-to-floor and wall-to-wall coverage with no blind spots.



COVERT LOW LIGHT COLOR AND IR PERFORMANCE

The camera delivers extreme color sensitivity and IR illumination that is imperceptible to the human eye.

SPECIFICATIONS

Camera	
Image Sensor	1/2.8" BSI CMOS
Sensor Resolution	2048 x 1536
Scanning Mode	Progressive
Sensitivity	0.02 (color)/0.01 (BW), 0 Lux with IR illuminator ON, measured at 30 IRE
Lens Type	2.1mm, 120° HFOV x 90° VFOV, F1.8, D/N
AES	1/1.75 to 1/10,000 (auto)
DSS	max. shutter 1/7.5(6.25)-1/60(50) / min.
White Balance	Auto / ATW / Manual / One Push
AGC	Auto
BLC	On / Off
WDR	On / Off
Noise Reduction	3D
Tamper Detection	Yes
Privacy Zones	Yes
Video Motion Detection	Yes
Day/Night Mode	Yes
Mechanical IR Cut Filter	Yes
Signal to Noise Ratio	±50 dB
ONVIF Compliance	Onvif Profile S & G
Audio Intensity Detection	Yes
Video	
Compression	Fully compliant multi-stream H.264 main/high profile + MJPEG
Max Performance	H.264 30/25 fps@QXGA + SVGA(NTSC/PAL) or H.264 15/12 fps@QXGA + 1280x960 + SVGA (NTSC/PAL)
Resolution Range	Scalable from SVGA to 3MP
Bandwidth	Configurable between 64Kbps and 20Mbps
Rate Control	CVBR
SD Card Recording	microSDXC up to 128GB (Class 10)
IR Illuminator	
Distance	up to 10 m (33 ft.)
Angle of illumination	Full 60°
LED Type	high efficiency SMD
Peak Emission Wavelength (nm)	940

Network	
Network Protocols	TCP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv4, IPv6, SSL, LDAP
Ethernet	10/100, auto sensing, half / full duplex (RJ45)
Remote Configuration	via web browser or supported video management software
Firmware Upgrade	Flash memory for upgrade of camera firmware over the network
Supported Web Browser	Internet Explorer 10+, Firefox 50+, Chrome 55+
Security	User account with password protection and IP filter
Audio	
Input	Built in Microphone, G.711 a/μ-law, AAC support
Output	Yes (from HW revision 02.00)
Alarm	
Input	1 Dry Alarm Contact
Output	1 Relay Contact
Physical	
Enclosure	IK10+ 50 Joule Impact Resistant / IP66
Dimensions	184 x 179 x 59 mm
Unit Weight	1.21kg(2.67 lbs.)
Mechanical	
Lens / IR Window	IK10 Vandal Resistant Polycarbonate
Lens Window Transmittance	45%
Electrical	
Input Voltage	802.3af PoE
Power Consumption	3.4W / 9.4W with heater and IR
Power Connection	PoE
Environmental	
Operating Temperature	-40°C to 50°C (-40°F to 122°F)
Storage Temperature	-40°C to 60°C (-40°F to 140°F)
Humidity	90% (non-condensing)
Warranty & Regulatory	
Warranty	According to FLIR RMA Policy and Process Notice document
USA	UL 60950, FCC Part 15 (subpart B, class A)
International	CE marked, EN61000-6-3 & EN50130-4, RoHS, RCM
MTBF (hrs)	382,189

Camera Ordering Information

Type	Series	Camera Resolution	Lens Options	Environmental	IR Illuminator
CC	31	03	0	1	I
Corner Camera	31 = Ariel Gen II	03 = 3 MP	0 = 2.1mm	1 = IP66 Vandal with Heater	I = 60° Illuminator

Specifications are subject to change without notice.
For the most up-to-date specs, go to www.flir.com

CORPORATE HEADQUARTERS

27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 877.773.3547

FLIR SECURITY SYSTEMS, INC.

65 Challenger Rd, Suite 201
Ridgefield Park, NJ 07660
PH: +1 201.368.9700

FLIR UK

7 Lancaster Court
High Wycombe, HP 123ht
PH + 44 (0) 1494.430248
F + 44 (0) 1494.446928

FLIR CANADA

FLIR Systems - Canada
250 Royal Crest Court
Markham, Ontario,
Canada L3R 3S1
PH: +1 888.425.6739

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2019 FLIR Systems, Inc. All rights reserved. Rev. 08/14/19

19-0582-SEC-ENT Ariel Corner Camera Datasheet A4



The World's Sixth Sense®