



THERMAL MSX® VIDEOSCOPE KIT WITH RECTANGULAR PROBE TIP

FLIR VS290-32™

The FLIR VS290-32 is an industrial thermal and visual videoscope designed to help professionals quickly and safely find hidden dangers in difficult-to-access locations, especially underground electrical distribution vaults. Featuring a 160 × 120 true thermal imager and FLIR MSX® (Multi-Spectral Dynamic Imaging), the VS290-32 enables users to catch hot spots before a failure occurs to maintain uptime. The 2 m camera probe makes it possible to easily inspect through small openings – improving productivity and reducing diagnostic time. Plus, the CAT IV 600 V safety rating makes the VS290-32 a rugged and versatile tool for the most demanding environments in utility, manufacturing, and building maintenance applications.

www.flir.com/VS290-32



INSPECT INACCESSIBLE AREAS SAFELY

Quickly find hidden faults without entering difficult-to-access locations and other hard-to-reach spaces

- Troubleshoot problems from a safe distance with the 160 × 120 true thermal imager and 2 MP visual camera
- Easily maneuver the narrow 2 m field-replaceable camera probe to inspect underground electrical distribution vaults, inside large gearboxes, motors, attics, crawl spaces, and other industrial applications
- Instantly recognize the location of a temperature issue with FLIR MSX, which extracts scene details from the built-in visual camera and embosses them onto the full thermal image



IDENTIFY, DOCUMENT, AND SHARE

Improve workflow and communicate potential issues before they become major problems

- View findings clearly on the large 3.5-inch color display, and use color alarms (isotherms) to quickly identify areas of concern
- Save images and videos using the included SD memory card, and upload to a PC via USB-C Cable
- Quickly create and share reports with team members to prioritize repairs using FLIR Thermal Studio



VERSATILE, RUGGED, AND RELIABLE

Use the VS290-32 in the most demanding environments

- Provides a high level of protection against dust and water (IP67 rated camera tip, IP54 rated base unit and probe)
- Easily replace the camera probe while in the field
- Conduct electrical inspections safely (CAT IV 600 V rated)

SPECIFICATIONS

Imaging and optical data		Image storage and visual camera	
IR resolution	160 × 120 pixels	Storage capacity	Removable SD card (16 GB)
Digital image enhancement	Yes, MSX®	Image file format	Radiometric JPEG
Thermal sensitivity/NETD	<100 mK	Visual camera resolution	2 MP
IR Field of view (FOV)	57° × 44°	Visual camera field of view (FOV)	83°
Minimum focus distance	0.15 m	Worklight	Bright LED
Image frequency	8.7 Hz	Data communication interface	
Focus	Fixed	USB	USB Type-C: data transfer/power
Focal plane array/spectral range	Uncooled microbolometer/7.5–14 μm	Additional data	
Detector pitch	12 μm	Battery type	Rechargeable 3.7 V Li-ion
Image presentation		Battery operating time	>5 hours (full LCD brightness and worklight on)
Display resolution	320 × 240 pixels	Probe length	2 m (6.6 ft)
Screen size	3.5 in	Probe tip shape	Rectangular (side-viewing camera)
Color palettes	Iron, Rainbow, Gray, Below alarm, Above alarm	Weight (including battery)	Complete kit with case: 13 kg (28.66 lb) Display: 640 g (1.41 lb) Probe: 470 g (1.04 lb)
Image modes	IR only, Visual only, MSX	Size (L × W × H)	Complete kit with case: 120 × 48 × 20 cm (47 × 18.90 × 7.87 in) Display: 26.4 × 11 × 11 cm (10.4 × 4.3 × 4.3 in) Probe: 212.2 × 0.69 cm (83.5 × 0.3 in) Probe tip: 74.16 × 40.52 × 11 mm (2.9 × 1.6 × 0.4 in)
Gallery	Yes	Box contents	
Measurement and analysis		Videoscope display (VS290-00), thermal MSX camera probe (VSC-IR32), two rechargeable batteries (T199330ACC), battery charger (T199425ACC), power supply for battery charger (T911633ACC), SD card, USB cable (T911631ACC), wrist strap, hard case, printed documents	
Object temperature range	–10 to 400°C (14 to 752°F)		
Measurement accuracy	At ambient temp. 15 to 35°C (59 to 95°F) and object temp. above 0°C (32°F) 0 to 100°C (32 to 212°F): ±3°C (±5.5°F) 100 to 400°C (212 to 752°F): ±3%		
Spotmeter	1 in live mode		
Measurement presets	No measurement, center spot, hot spot, cold spot		
Emissivity correction	3 pre-set and 1 custom emissivity setting		

CORPORATE HEADQUARTERS

FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

LATIN AMERICA

FLIR Systems Brasil
Av. Antonio Bardella, 320
Sorocaba, SP 18085-852
Brasil
PH: +55 15 3238 8070

NASHUA

FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

CANADA

FLIR Systems, Ltd.
3430 South Service Road, Suite 103
Burlington, ON L7N 3J5
Canada
PH: +1 800.613.0507

www.flir.com
NASDAQ: FLIR

Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2020 FLIR Systems, Inc. All rights reserved. Rev. 10/21/20

20-1120-INS



The World's Sixth Sense®